

TORIAN® SuperSuede™

Description

Torian® SuperSuede™ is a premium self-adhesive microfiber suede interior wrap film with a luxurious, tactile Alcantara-style texture. Specifically designed for interior customisation, this film combines aesthetic elegance with conformability and ease of application for a wide range of surfaces including dashboards, door panels, trims, consoles, and furniture.

Face Film

Film Type:	92% Terylene (PET fibre) and 8% Polyurethane
Surface Finish:	Matt finish
Film Thickness:	$200\text{gr/m}^2 \pm 10\text{gr/m}^2$
Tenacity:	105D x 150D
Tensile Strength:	Warp: 480 / Weft 380
Opacity:	65%

Adhesive

Type:	two-component high-tack clean removable glue
Thickness:	$30\mu\text{m} \pm 2\mu\text{m}$
Initial Tack:	$>10\text{N}/25\text{mm } 180^\circ$
Holding Tack:	$>18\text{N}/25\text{mm } 180^\circ$

User Instructions

Application Temperature:	+15° C to +35° C
Service Temperature:	-30° C to +90° C

There is an application guide available for this product.

Liner

140grm² kraft paper silicone coated liner (grid printed)

Durability

Indoor use only.

Benefits & Features

Premium Alcantara-style finish – authentically replicates the look and feel of real suede/Alcantara.
Flexible conformability – stretches and moulds to complex curves, contours, and interior detailing.
Non-reflective matte texture – reduces glare, ideal for dashboards and cockpits.
Removable without residue – designed for professional application and clean removal.
Ideal for automotive, marine, and aviation interiors – versatile for multiple applications.
Customisation flexibility – perfect for dashboards, door panels, centre consoles, headliners, and trims.

Storage

Rolls should be stored vertically, in their original packaging and in a dust free environment. Typically, with relative humidity at max. 50% and between +15°C to +25°C for a maximum of up to 1 year.

Roll Dimensions

1520mm x 15m (10kg) (SUEDE900 / SUEDE877 / SUEDE200 / SUEDE300 / SUEDE430 / SUEDE445)
1400mm x 15m (9kg) (SUEDE060 / SUEDE068 / SUEDE182 / SUEDE295)

Torian® Warranty

Due to the great variety of substrates and the growing number of new applications, the installer must check the suitability of the product for each application. In case of doubt, please request an expert evaluation of the compatibility of the film and the surface in question. All of the published information is based on measurements regularly performed in the laboratory. The published information does not however constitute a binding guarantee. The seller cannot be held liable for indirectly related damages and assumes no liability for claims that are higher than the replacement value of the purchased product. All specifications are subject to potential changes without prior notice.